

AMENDMENTS TO THE CLAIMS

1-25. (Cancelled)

26. (Currently Amended) A semiconductor device, comprising:

a metallic layer over a substrate;

a dielectric layer over said metallic layer;

a via hole extending through the dielectric layer to a surface of the metallic layer;

~~a first~~ <sup>delete</sup> titanium aluminide layer lining at least a bottom of the via hole;

a ~~second~~ titanium aluminide tungsten layer ~~or a titanium layer~~ at least on sides of said via hole; and

a conductive material on the ~~first~~ titanium aluminide layer, said conductive material and said ~~first~~ titanium aluminide layer being in contact at an interface, said interface being substantially free from tensile stress between said ~~first~~ titanium aluminide layer and said conductive material.

27. (Currently Amended) A semiconductor device, comprising:

an aluminum layer over a substrate;

a dielectric layer over the aluminum layer;

a via hole extending through the dielectric layer to a surface of the aluminum layer;

a conductive plug material on the titanium tungsten compound layer; and

a second metallic layer on the second dielectric layer and electrically connected to the conductive plug material.

29. (Currently Amended) The semiconductor memory device as recited in claim 28, wherein ~~the titanium compound layer is titanium nitride~~ the titanium aluminide layer is also on the sides of said via.

30. (Original) The semiconductor memory device as recited in claim 28, wherein the first metallic layer comprises aluminum.

31. (Original) The semiconductor memory device as recited in claim 28, wherein the memory circuit includes a SRAM cell.

32. (Original) The semiconductor memory device as recited in claim 28, wherein the memory circuit includes a DRAM cell.

33. (Currently Amended) A memory module, comprising:

a substrate comprising a circuit board;

a plurality of memory chips mounted on the substrate and connected to form a memory circuit, wherein one or more of the memory chips comprise a random access memory (RAM) fabricated on a semiconductor substrate comprising:

a first metallic layer over the semiconductor substrate;

an antireflective coating over the first metallic layer;

a dielectric layer over the antireflective coating;

a via hole extending through the dielectric layer and the antireflective coating to a surface of the first metallic layer;

a titanium aluminide layer lining at least a bottom of the via hole;

~~a titanium layer lining sides of the via hole;~~

a titanium tungsten compound containing layer over the titanium aluminide layer ~~and the titanium layer~~, said titanium tungsten compound layer being in contact with said titanium aluminide layer, wherein said titanium tungsten compound layer experiences approximately no tensile stress from said titanium aluminide layer;

a conductive plug material formed over the titanium tungsten compound layer, said conductive plug comprising a material selected from the group consisting of molybdenum, titanium, and tantalum;

a second metallic layer on the dielectric layer and electrically connected to the conductive plug material; and

a connector on the semiconductor substrate and wired to said memory circuit.

34. (Currently Amended) A memory module, comprising:

a substrate comprising a circuit board;

a plurality of memory chips mounted on the substrate and connected to form a memory circuit, wherein one or more of the memory chips comprise a random access memory (RAM) fabricated on a semiconductor substrate comprising:

a metallic layer over the semiconductor substrate;

a dielectric layer over the metallic layer;

a via hole extending through the dielectric layer to a surface of the metallic layer;

a ~~first~~ titanium aluminide layer lining ~~at least~~ a bottom and sides of the via hole;

a ~~second~~ titanium ~~aluminide~~ tungsten layer ~~or a titanium layer lining sides of the via hole~~ over said first titanium aluminide layer; and

a conductive material ~~on~~ over the ~~first~~ titanium aluminide layer, wherein said conductive material and said ~~first~~ titanium aluminide layer are in contact at an interface having approximately no tensile stress from said ~~first~~ titanium aluminide layer; and

a connector on the semiconductor substrate and wired to said memory circuit.

35. (Currently Amended) A memory module, comprising:

a substrate comprising a circuit board;

a plurality of memory chips mounted on the substrate and connected to form a memory circuit, wherein one or more of the memory chips comprise a random access memory (RAM) fabricated on a semiconductor substrate comprising:

an aluminum layer over the semiconductor substrate;

a random access memory (RAM) fabricated on a semiconductor chip communicating with the processor and comprising:

a first metallic layer over a substrate;

a dielectric layer over the first metallic layer;

a via hole extending through the dielectric layer to a surface of the first metallic layer;

a titanium aluminide layer lining a bottom and sides of the via hole;

a titanium ~~compound~~ tungsten containing layer over the titanium aluminide layer;

a conductive plug material formed on the titanium ~~compound~~ tungsten layer; and

a second metallic layer over the dielectric layer and electrically connected to the conductive plug material.

38. (Currently Amended) A computer system, comprising:

a processor; and

a random access memory (RAM) fabricated on a semiconductor chip communicating with the processor and comprising:

a metallic layer over a substrate;

an antireflective coating over the metallic layer;

a dielectric layer over the antireflective coating;

a via hole extending through the dielectric layer and the antireflective coating to a surface of the metallic layer;

~~a first~~ titanium aluminide layer lining at least a bottom of the via hole;

a ~~second~~ titanium aluminide tungsten layer ~~or a titanium layer~~ lining at least the sides of the via hole; and

a conductive material on the ~~first~~ titanium aluminide layer, wherein said conductive material is in contact with said ~~first~~ titanium aluminide layer at an interface, said interface being substantially free of tensile stress between said ~~first~~ titanium aluminide layer and said conductive material.

39. (Currently Amended) A computer system, comprising:

a processor; and

a random access memory (RAM) fabricated on a semiconductor chip communicating with the processor and comprising:

an aluminum layer over a substrate;

a dielectric layer over the aluminum layer;

a via hole extending through the dielectric layer to a surface of the aluminum layer;

a titanium aluminide layer lining a bottom of the via hole;